

SIMPSON DOORS IN STOCK



© ROB KAROSIS / ROBKAROSIS.COM



© ROB KAROSIS / ROBKAROSIS.COM



BUNGALOW SERIES®

Simpson Bungalow Series doors are stocked 1-3/4", 3'0" x 6'8", 1-7/16" Innerbond® beaded v-groove double hip-raised panels and UltraBlock® technology – 5-year warranty. Matching sidelights are stocked 1-3/4", 1'2" x 6'8" with 1-7/16" Innerbond beaded v-groove double hip-raised panels. All glazed doors offered with 3/4" IG. This collection is offered in Douglas Fir.



7214
Fir
2'8", 3'0"

M 7215
Fir

7226
Fir

M 7217
Fir

7218
Fir
2'8", 3'0"


M 7228
Fir
2'8", 3'0"

M 7219
Fir

7304
Fir

M 7324
Fir



 UltraBlock® technology included – 5 year warranty



NANTUCKET® COLLECTION

Simpson Nantucket Collection doors are stocked 1-3/4", 3'0" x 6'8" (unless otherwise noted) and matching sidelights are stocked 1-3/4", 1'2" x 6'8". All doors offered with 3/4" IG with Low-E. This collection is offered in both Douglas Fir and Sapele Mahogany, as shown. All Nantucket Collection doors come with a 10-year warranty with no building overhang required.



77130
Fir
1-7/16" DHRP



77175
Fir
1-7/16" DHRP



77662
Fir
1-7/16" DHRP



77663
Fir
1-7/16" DHRP



77660
Fir
1-7/16" DHRP
2'8", 3'0"



77660 Shaker
Fir
3/4" FP
2'8", 3'0"



77944
Fir
1-7/16" DHRP
2'8", 3'0"



77703
Fir
1-7/16" DHRP



77506
Fir
1-7/16" DHRP
2'8", 3'0"



77506 Shaker
Fir
3/4" FP
2'8", 3'0"



77512
Fir
1-7/16" DHRP
2'8", 3'0"



77512 Shaker
Fir
3/4" FP
2'8", 3'0"




77015
Fir
1-7/16" DHRP
2'8", 3'0"




77705
Fir
1-7/16" DHRP

FP = FLAT PANEL | DHRP = INNERBOND® DOUBLE HIP-RAISED PANEL



77662
Shown in Douglas fir with 77663
sidelights with raised panels





77130
Mahogany
1-7/16" DHRP



77175
Mahogany
1-7/16" DHRP



77662
Mahogany
1-7/16" DHRP



77663
Mahogany
1-7/16" DHRP



77994
Mahogany
1-7/16" DHRP
2'8", 3'0"



77703
Mahogany
1-7/16" DHRP



77015
Mahogany
1-7/16" DHRP
2'8", 3'0"



77705
Mahogany
1-7/16" DHRP



77660
Mahogany
1-7/16" DHRP
2'8", 3'0"



77660 Shaker
Mahogany
3/4" FP
2'8", 3'0"



77506
Mahogany
1-7/16" DHRP
2'8", 3'0"



77506 Shaker
Mahogany
3/4" FP
2'8", 3'0"




77512
Mahogany
1-1/4" DHRP
2'8", 3'0"



TRADITIONAL EXTERIOR DOORS

Simpson Traditional Exterior doors are stocked 1-3/4", 3'0" x 6'8" with 1-7/16" Innerbond® double hip-raised panels, unless otherwise noted. Matching sidelights are stocked 1-3/4", 1'2" x 6'8" with 1-7/16" Innerbond double hip-raised panels. All glazed doors offered with 3/4" IG, unless otherwise noted. This collection is offered in Douglas Fir, Sapele Mahogany, American Oak, and Ponderosa Pine as noted.




4416
Fir
V-groove




3044
Colonial IV
Fir
1-1/4" Innerbond DHRP



3130
Colonial VI
Fir
1-1/4" Innerbond DHRP



4040
Tudor I
Fir
1-1/4" Innerbond DHRP



4230
Fir
Bullion Glass
1-1/4" Innerbond DHRP




7598
Bellaire®
Fir
Beveled Glass



7599
Fir
Beveled
Glass



7132
Fir
2'8", 3'0"




7132
Pine




7132
Mahogany
2'8", 3'0"



7130
Fir
2'8", 3'0"; 3'0" x 7'0"



7130
Pine
2'8", 3'0"; 3'6",
3'0"; 3'6" x 7'0"



7130
Mahogany



7705
Mahogany
1'0", 1'2", 3'6"



37120
Fir SDL
2'8", 3'0"



7134
Fir
2'8", 3'0"



7344
Fir
2'8", 3'0"; 3'0" x 7'0"



7344
Mahogany
2'8", 3'0"



2044
Knotty Alder
3/4" DHRP




2044
Oak / Fir
3/4" DHRP



2130
Fir
3/4" DHRP
2'6" x 2'8", 3'0",
3'0" x 7'0"




2130
Knotty Alder
3/4" DHRP




2130
Oak
3/4" DHRP




1044
Pine
3/4" DHRP
2'8", 3'0"




100
Pine
3/4" DHRP
2'6", 2'8", 3'0" x 6'6";
2'0", 2'4", 2'6", 2'8",
3'0" x 6'8";
2'6", 2'8", 3'0" x 7'0"



2132
Fir
3/4" DHRP
2'8", 3'0", 3'0" x 7'0"



2134
Fir
2'8", 3'0", 3'0" x 7'0"




EXTERIOR FRENCH & SASH DOORS

INSULATED GLASS

Simpson Insulated Exterior French & Sash doors are stocked 1-3/4", 3'0" x 6'8" with 1-7/16" Innerbond® double hip-raised panels and UltraBlock® technology – 5-year warranty, unless otherwise noted. Matching sidelights are stocked 1-3/4", 1'2" x 6'8" with 1-7/16" Innerbond double hip-raised panels, unless otherwise noted. All doors incorporate 3/4" insulated glass (IG) units. This collection is offered in Douglas Fir, Sapele Mahogany, Ponderosa Pine and American Red Oak as shown.



7001  Fir
2'0"



7001  Pine
2'0"



7002  Fir
2'6", 2'8", 3'0";
3'0" x 7'0"




7701  Fir
1'0", 1'2";
1'0",
1'2" x 7'0"




7002  Pine
2'6", 2'8", 3'0";
2'6", 2'8", 3'0" x 7'0"





7701  Pine
1'0", 1'2"




37010  SDL Fir
2'0"




7010  TDL Fir
2'0"




37010  SDL Pine
2'0"



7010  TDL Pine
2'0"



37015  SDL Fir
2'6", 2'8", 3'0";
3'0" x 7'0"



37705  SDL Fir
1'0", 1'2"; 1'0"
1'2" x 7'0"




37015  SDL Pine
2'6", 2'8", 3'0"



37705  SDL Pine
1'0", 1'2"





7015  TDL Fir
2'0", 2'6", 2'8", 3'0";
3'0" x 7'0"



7705  TDL Fir
1'0", 1'2";
1'0", 1'2" x 7'0"




7109  TDL Fir
2'6", 3'0"




37512  SDL Fir
2'6", 2'8", 3'0"



37804  SDL Fir
1'0", 1'2"




7512  TDL Fir
2'6", 2'8", 3'0"



7804  TDL Fir
1'0", 1'2"




7015  TDL Pine
2'6", 2'8", 3'0"



7705  TDL Pine
1'0", 1'2"



7512 TDL M
Pine




37506 SDL M
Fir
2'6", 2'8", 3'0"




7044
Fir
2'6", 2'8", 3'0"



7702 M
Fir
10", 10", 12"




7044 M
Pine
2'8", 3'0"



37944 SDL M
Fir
2'6", 2'8", 3'0";
3'0" x 7'0"




37703 SDL M
Fir
10", 10", 12"



37944 SDL M
Pine
2'8", 3'0"




37703 SDL
Pine
10", 12"



7944 TDL
Fir
2'6", 2'8", 3'0";
3'0" x 7'0"



7703 TDL M
Fir
10", 10", 12";
12" x 7'0"




7944 TDL M
Knotty Alder
3'0", 3'0" x 7'0"



7944 TDL
Mahogany
2'8", 3'0"



7703 TDL M
Mahogany
10", 12"



7944 TDL
Pine
2'8", 3'0"



7703 TDL M
Pine
10", 12"



7703 TDL
Oak



7031 M
Fir
2'8", 3'0"



7113 TDL M
Pine
2'8", 3'0"



7662 TDL
Fir
2'8", 3'0";
3'0" x 7'0"



7663 TDL M
Fir
10", 12";
10", 12" x 7'0"



7662 TDL M
Knotty Alder
3'0", 3'0" x 7'0"
Shown with 9541 dentil shelf



7860 TDL
Fir



7260 TDL M
Fir



7662 TDL M
Mahogany
2'8", 3'0"



7663 TDL M
Mahogany
10", 12"



7660 TDL M
Mahogany
2'8", 3'0"



7701 M
Mahogany
10", 12"



7666 TDL M
Shaker Pine
3/4" FP
2'8", 3'0"
Shown with 9541
dentil shelf



7663 TDL M
Shaker Pine
3/4" FP
10", 12"


EXTERIOR FRENCH & SASH DOORS

SINGLE-GLAZED

Simpson Single-Glazed Exterior French & Sash doors are stocked 1-3/4", 3'0" x 6'8" with 3/4" double hip-raised panels, unless otherwise noted. All doors offered with 1/8" SG. This collection is offered in Douglas Fir and Ponderosa Pine as shown.




1510
Fir
2'0", 2'0" x 7'0"




1310
Pine
2'0"



1515
Fir
2'4", 2'6", 2'8", 3'0",
3'0" x 7'0"




1315
Pine
2'6", 2'8", 3'0",
3'0" x 7'0"




117
Fir
2'6", 2'8", 3'0",
3'0" x 7'0"




318
Fir
2'6", 2'8", 3'0"




418
Fir
2'6", 2'8", 3'0",
3'0" x 7'0"



944
Fir
2'6", 2'8", 3'0",
2'10" x 6'10",
3'0" x 7'0"



944
Pine
2'6", 2'8" x 6'6", 2'6",
2'8", 3'0" x 6'8",
3'0" x 7'0"




2035
Fir
2'6", 2'8", 3'0"




2011
Dutch Door
Pine
2'6", 2'8", 3'0"



2013
Dutch Door
Pine
2'8", 3'0"



4011
Dutch Door
Pine
3'0"



4013
Dutch Door
Pine
3'0"



944
Shown in pine

DOORS WITH WATERBARRIER® TECHNOLOGY



Simpson doors with WaterBarrier offer protection in tough exposures. All doors with WaterBarrier technology come with a 5-year warranty with no building overhang required. WaterBarrier technology features a medium density overlay over the exterior surface of the door with PVC bars and glazing beads, providing a beautiful surface for paint. And all with the beauty of Douglas Fir on the inside of the door. All doors with WaterBarrier technology are stocked 1-3/4", 3'0" x 6'8" with 1-7/16" Innerbond® double hip-raised panels, 3/4" IG with Low-E and UltraBlock® technology. Matching sidelights are stocked 1-3/4", 1'2" x 6'8".



37512 WB
Fir
2'6", 2'8", 3'0"

37506 WB
Fir
2'6", 2'8", 3'0"

37504 WB
Fir
2'6", 2'8", 3'0"

37015 WB
Fir
2'6", 2'8", 3'0";
3'0" x 7'0"

37705 WB
Fir
1'2", 1'2" x 7'0"

7002 WB
Fir
2'6", 2'8", 3'0"

37944 WB
Fir
2'8", 3'0"

37662 WB *
Fir
3'0"



UPGRADE ANY SPECIAL ORDER DOOR WITH WATERBARRIER® TECHNOLOGY


- Medium Density Overlay (MDO) over the exterior surface of the door (to be painted)
- Can be combined with any wood species for the inside of the door (can be stained or painted)
- **5-year warranty with no building overhang requirement**
- Available for virtually any Simpson door
- For more info, visit simpsondoor.com/waterbarrier

WATERBARRIER® TECHNOLOGY (PATENT PENDING)

PVC glazing bead and SDL bars on exterior side. Wood bars on interior side.

Primed Medium Density Overlay for flat surfaces

Innerbond® double hip-raised panels have a water-resistant primer




WEATHER SEAL™ PROCESS

Entire stile-and-rail joints coated and bonded to decrease the possibility of water infiltration

ULTRABLOCK® TECHNOLOGY

Composite block material finger-jointed into the bottom of the stiles



37015

with custom transom and WaterBarrier® and UltraBlock® technologies

TRANSOMS

Simpson Exterior Transoms can be paired with a variety of Simpson doors and sidelights to create a beautiful overall door unit. Transoms are stocked 1-3/4" with 3/4" IG. This collection is offered in Douglas Fir and Ponderosa Pine.

FIR TRANSOMS FOR WOOD ENTRY UNITS

Clear Insulating Glass (IG) Units:

- Solid Bar True Divided Light

Low-E Argon Insulating Glass (LE) Units:

- Simulated Divided Light (SDL)

Wood Frame:

FJP, Pine, Oak, & Fir

- Transom Sash unprimed Fir

- All Transom Sash 12" high x 1-3/4" thick

FIR	SASH DIMENSIONS	FIR SASH NUMBER	TRANSOM DESIGN DOOR COMBINATION	ACTUAL TRANSOM FRAME SIZE (NO CASING)
		F-7743-IG F-37743-LE	3-0 Single Door with 4-1/2" Stiles	3' 1-1/2" x 13-1/2"
		F-7753-IG F-37753-LE	3-0 Single Door with 5-1/2" Stiles	3' 1-1/2" x 13-1/2"
		F-7745-IG F-37745-LE	5-4 Single Door with 4-1/2" Stiles	5' 6-1/2" x 13-1/2"
		F-7755-IG F-37755-LE	5-4 Single Door with 5-1/2" Stiles	5' 6-1/2" x 13-1/2"
		F-7745-IG F-37745-LE	6-0 Single Door with 4-1/2" Stiles	6' 2-1/2" x 13-1/2"
		F-7755-IG F-37755-LE	6-0 Single Door with 5-1/2" Stiles	6' 2-1/2" x 13-1/2"
		F-7715-IG F-37715-LE	1-0 / 3-0 / 1-0 Door with 2 Sidelights Continuous Sill	5' 4-1/2" x 13-1/2"
		F-7725-IG F-37725-LE	1-2 / 3-0 / 1-2 Door with 2 Sidelights Continuous Sill	5' 8-1/2" x 13-1/2"
ROUGH OPENING: Width - Same as door unit *Height - Door unit with transom applied 8'-0"		*Based on 6'8" door unit with standard sill (inswing). Deduct 1-1/2" from height for public access sill unit.		

PINE TRANSOMS FOR WOOD ENTRY UNITS

Clear Insulating Glass (IG) Units:

- Solid Bar True Divided Light

Low-E Argon Insulating Glass (LE) Units:









- Simulated Divided Light (SDL)

Wood Frame:

FJP, Pine, Oak, & Fir

- Transom Sash unprimed Pine

- All Transom Sash 12" high x 1-3/4" thick

PINE	SASH DIMENSIONS	PINE SASH NUMBER	TRANSOM DESIGN DOOR COMBINATION	ACTUAL TRANSOM FRAME SIZE (NO CASING)
	3'-0"	F-7745-IG F-37745-LE	3-0 Single Door with 4-1/2" Stiles	3' 1-1/2" x 13-1/2"
	3'-0"	F-7755-IG F-37755-LE	3-0 Single Door with 5-1/2" Stiles	3' 1-1/2" x 13-1/2"
	5'-5"	F-7749-IG F-37749-LE	5-4 Double Door with 4-1/2" Stiles	5' 6-1/2" x 13-1/2"
	5'-5"	F-7759-IG F-37759-LE	5-4 Double Door with 4-1/2" Stiles	5' 6-1/2" x 13-1/2"
	6'-1"	F-7740-IG F-37740-LE	6-0 Double Door with 4-1/2" Stiles	6' 2-1/2" x 13-1/2"
	6'-1"	F-7750-IG F-37750-LE	6-0 Double Door with 5-1/2" Stiles	6' 2-1/2" x 13-1/2"
	5'-3"	F-7719-IG F-37719-LE	1-0 / 3-0 / 1-0 Door with 2 Sidelights Continuous Sill	5' 4-1/2" x 13-1/2"
	5'-7"	F-7729-IG F-37729-LE	1-2 / 3-0 / 1-2 Door with 2 Sidelights Continuous Sill	5' 8-1/2" x 13-1/2"
ROUGH OPENING: Width - Same as door unit *Height - Door unit with transom applied 8'-0"		*Based on 6'8" door unit with standard sill (inswing). Deduct 1-1/2" from height for public access sill unit.		



INTERIOR PANEL & BIFOLD DOORS

Simpson Interior Panel and Bifold doors are stocked 1-3/8" and 6'8" height, and at the widths indicated. This collection is offered in Douglas Fir, Knotty Alder and American Red Oak as shown. All Simpson interior doors are backed by a 10-year warranty.



82 Fir
3/4" DHRP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"



465 Fir
3/4" DHRP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"




82 KA
3/4" DHRP
1'6", 2'0", 2'2", 2'4",
2'6", 2'8", 3'0"




465 KA
3/4" DHRP
2'0", 2'4", 2'6", 2'8",
3'0"



44 Fir
3/4" DHRP
1'6", 2'0", 2'2", 2'4", 2'6",
2'8", 3'0"



66 Fir
3/4" DHRP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"




63 Bifold Fir
3/4" DHRP
2'0", 2'6", 3'0"
Available in 4 door
units at 4'0", 5'0", 6'0"




66 Oak
3/4" DHRP
1'0", 1'4", 1'6", 1'8", 2'0",
2'2", 2'4", 2'6", 2'8", 3'0"



63 Bifold Oak
3/4" DHRP
2'0", 2'6", 3'0"
Available in 4 door
units at 4'0", 5'0", 6'0"




55 Fir
3/4" DHRP
1'6", 2'0", 2'2", 2'4",
2'6", 2'8", 3'0"




20 Fir
3/8" FP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"



82 Fir
3/8" FP
1'0", 1'4", 1'6", 1'8",
1'10", 2'0", 2'2", 2'4",
2'6", 2'8", 3'0"



1182 Fir Chalkboard
1/4" Magnetic
Chalkboard Panel
2'6"



30 Fir
3/8" FP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"




720 Shaker Fir
3/8" FP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"



782 Shaker Fir
3/8" FP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"




730 Shaker Fir
3/8" FP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"




760 Shaker Fir
3/8" FP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"



744 Shaker Fir
3/8" FP
2'0", 2'4", 2'6", 2'8",
3'0"



762 Shaker Fir
3/8" FP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"



755 Shaker Fir
3/8" FP
1'6", 2'0", 2'4", 2'6",
2'8", 3'0"

INTERIOR FRENCH & SASH DOORS


Simpson Interior French and Sash doors are stocked 1-3/8", 6'8" height and 1/8" single-glazed. This collection is offered in Douglas Fir and American Red Oak at the sizes indicated. All Simpson interior doors are backed by a 10-year warranty.



117
Fir
3/4" DHRP
2'6" x 6'0", 2'6",
2'8" x 6'8"



318
Fir
3/4" DHRP
2'6", 2'8"



944
Fir
3/4" DHRP
2'6", 2'8", 3'0"




1501 Shaker
Fir
White Laminate
2'0", 2'4", 2'6", 2'8",
3'0"



1590 Pantry
Fir
2'0", 2'4", 2'6"



1592 Wheat
Fir
2'6"



1505
Fir
1'6", 2'6", 2'8", 3'0"



1310
Fir
2'0"



1310
Oak
2'0"



1580
Fir
2'6", 2'8", 3'0"




1315
Fir
2'4", 2'6", 2'8", 3'0"



1315
Oak
2'4", 2'6", 2'8", 3'0"



1309
Fir
2'6", 3'0"



84-SL09 Shaker
Fir
Satin Etch
1'6", 2'0", 2'4", 2'6", 2'8",
3'0"



1590 PANTRY
Shown in Douglas Fir




REDI-SHIP® EXTERIOR


- Simpson Redi-Ship® doors are “almost in stock,”.
- Factory order with expedited lead time.
- Redi-Ship includes today’s most popular doors for both exterior and interior applications and supports the requests that in stock inventory does not cover.
- Redi-Ship doors are offered in the exact designs, sizes, species profiles and options as specified below.

FULL LITE DECORATIVE DOORS

Full Lite Decorative Doors are available for the Redi-Ship Program 1-3/4" thick, in both 3'0" x 6'8" and 3'0" x 8'0" in Douglas Fir with UltraBlock® technology – 5-year warranty. Sidelights available 1-3/4" thick, 1'2" x 6'8" and 8'0" in Douglas Fir.



PILLAR POINT®
Black Caming | 6903*,
6190* (left) and 6191*
(right) Sidelights



PILLAR POINT® 8'0"
Black Caming | 6903*, 6190*
(left) and 6191* (right)
Sidelights



COASTAL SURF®
Black Caming | 6901* (left),
6902* (right)



COASTAL SURF® 8'0"
Black Caming | 6901* (left),
6902* (right)



EMBARCADERO®
Silver Caming | 6468,
6469 Sidelight




EMBARCADERO® 8'0"
Silver Caming | 6468,
6469 Sidelight



PAMPLONA®
Black Caming | 6420*,
6421* Sidelight



PAMPLONA® 8'0"
Black Caming | 6420*,
6421* Sidelight



WATTSWORTH®
Black Caming | 6462,
6463 Sidelight



WATTSWORTH® 8'0"
Black Caming | 6462,
6463 Sidelight

*As viewed from exterior of home

CONTEMPORARY EXTERIOR DOORS

Simpson offers a variety of contemporary and modern-styled doors to fit today's architectural trends. And the following doors are available for the Redi-Ship® program, all 1-3/4" thick, 3'0" x 6'8" or 3'0" x 8'0" in Douglas Fir with shaker sticking and UltraBlock® technology – 5 year warranty. Sidelights available 1-3/4" thick, 1'2" x 6'8", and 8'0" in Douglas Fir with shaker sticking. And each door is available with your choice of two insulated glass types: **clear and white laminate.**



YOUR CHOICE OF CLEAR OR WHITE LAMINATE.

7002 | 7701 SL
Shaker sticking, shown with clear glass
3'0" x 6'8"

7002 | 7701 SL
Shaker sticking, shown with clear glass
3'0" x 8'0"

7405
Shaker sticking, shown with clear glass
3'0" x 6'8"

7409
Shaker sticking, shown with clear glass
3'0" x 6'8"

7421
Shaker sticking, shown with clear glass
3'0" x 6'8"

DOORS WITH WATERBARRIER® TECHNOLOGY

WaterBarrier® technology is Simpson's version of a clad door. It is a proven solution for doors in tough exposures and allows the beauty of a stained wood interior and a protected, painted surface on the exterior. Doors with WaterBarrier technology come with a 5-year warranty with no overhang requirement. These doors are available for the Redi-Ship Program 1-3/4" thick in Douglas Fir and in the designs and sizes indicated. UltraBlock technology is always included when WaterBarrier is ordered. And each door is available with your choice of two insulated glass types: **clear and clear with Low-E.**



YOUR CHOICE OF CLEAR OR CLEAR WITH LOW-E.

7001 WB
(Exterior Shown)
Available: 2'6" x 6'8", 2'8" x 6'8", 3'0" x 6'8"

7001 WB 8'0"
(Interior Shown)
Available: 2'6" x 8'0", 2'8" x 8'0", 3'0" x 8'0"

7002 WB 8'0"
(Interior Shown)
Available: 2'6" x 8'0", 2'8" x 8'0", 3'0" x 8'0"

7501 WB
(Exterior Shown)
Available: 2'8" x 6'8", 3'0" x 6'8"

7501 WB 8'0"
(Interior Shown)
Available: 3'0" x 8'0"

NANTUCKET® COLLECTION DOORS

Nantucket Collection doors feature solid, laminated construction and a modified mortise-and-tenon construction technique. The result is a beautiful wood door that will last no matter where you put it. These doors are available for the Redi-Ship Program 1-3/4" thick and in the sizes and wood species indicated. All Nantucket Collection doors feature a 10-year warranty with no overhang required.



77002
In Douglas Fir
3'0" x 6'8"

77002
In Sapele Mahogany
3'0" x 8'0"

77002
In Douglas Fir
3'0" x 8'0"

77002
In Sapele Mahogany
3'0" x 8'0"



REDI-SHIP® INTERIOR

· Simpson Redi-Ship® doors are “almost in stock,”.

· Factory order with expedited lead time.

· Redi-Ship includes today’s most popular doors for both exterior and interior applications and supports the requests that in stock inventory does not cover.

· Redi-Ship doors are offered in the exact designs, sizes, species profiles and options as specified below.

HEMLOCK



44 RP



43 RP Bifold



465 RP



45 RP Bifold



66 RP



63 RP Bifold



782 Shaker



702 Shaker
Bifold



760 Shaker



700 Shaker
Bifold

FIR



755 Shaker



1310



1315



1501 Clear



45 RP Bifold




700 Shaker
Bifold



701 Shaker
Bifold



1501 Clear



21 FP Bifold

KNOTTY ALDER



45 RP Bifold



43 RP Bifold



720 Shaker



701 Shaker
Bifold



760 Shaker



700 Shaker
Bifold



782 Shaker



702 Shaker
Bifold

OAK



44 RP



43 RP Bifold



760 Shaker



700 Shaker
Bifold



782 Shaker



702 Shaker
Bifold

MAPLE



44 RP 43 RP Bifold 66 RP 63 RP Bifold 760 Shaker 700 Shaker Bifold 782 Shaker 702 Shaker Bifold 1310 1315

REDI-PRIME® DECORATIVE FRENCH DOORS



8402 Newport 8403 Waterton 8404 Venetia® 8405 Windsor 8406 Prairiefield® 8411 Satin Etch 8421 Terrace Ridge® 8422 Newport 8423 Waterton



8424 Venetia® 8425 Windsor 8426 Prairiefield® 8450 Beveled Brass 8452 Normandy® 8462 Newport 8463 Waterton 8464 Venetia® 8465 Windsor



8466 Prairiefield® 8498 Kerrisdale® 8490 Pantry 8492 Grain 8493 Laundry 8494 Wine 8495 Media 8496 Border

REDI-PRIME® FRENCH DOORS



8001 8'0" 8010 8012 8'0" 8018 8'0"

REDI-PRIME® BIFOLDS



8700 Shaker 8705 Shaker


DOOR UNIT SPECS & OPTIONS

EXTERIOR WOOD DOORS

STANDARD DOOR UNIT FEATURES

- 4-9/16" Prime Wood Frame - Inswing
- Limited-Lifetime Warranty
- Brickmould Exterior Casing - Primed
- Compression Type Weatherstripping and Corner Seals
- Bulb and Fin Door Bottom
- Aluminum Sill (mill finish) - with Thermal Break, Hardwood Adjustable
- 4" x 4" Zinc Dichromate Hinges (dull brass color)
- Single Bore 2-3/8" Backset (2-3/8" Facebore)
- Double Door Units - White Aluminum Ultimate Astragal included (w/ Flush Bolts)

POPULAR DOOR UNIT OPTIONS



BROSCO's Lockguard Security Plate adds the strength of steel to the wood jamb, at the critical location of the latchbolt and deadbolt. Forced entry results in pressure at the latchbolt. A wood frame will usually splinter in this area before the hardware fails.

The Lockguard Security Plate, when attached to a wood frame along with a deadbolt, provides the best resistance to forced entry next to a steel frame.

This is a standard feature with the deadbolt prep option on BROSCO Single Wood Entry Units.

JAMBS

- Clear Pine, Clear Fir, Clear Oak and Clear Mahogany - various widths
- Vinyl Clad Wood Frame
- Composite; Primed, White Cap & Mahogany-Grained

CASING

- Primed or Clear Pine Flat (1-1/18" x 3-1/2"), Primed Cape Cod Flat (11/16" x 4-1/2") or Clear Cedar (1-1/16" x 3-1/2")
- Clear Pine, Oak and Mahogany Brickmould
- Composite Brickmould; Primed, White Cap & Mahogany-Grained
- Low-Maintenance PVC Trim
- Decorative PVC Entrance Trim

SILL

- Oak or Mahogany, Bronze, Satin Nickel or Brass Aluminum (Anodized Finish) or Public Access (aluminum)
- Sill Pan for Installation of 4-9/16" and 6-9/16" Walls - WeatherOut Flashing

HINGES

- Bright Brass Plated, Polished Chrome, Satin Chrome, Satin Nickel, Antique Nickel, Antique Brass, Antique Bronze, Dark Bronze, Primed, Black, Solid Brass and Stainless Steel

HARDWARE

- Door Viewer, Brass Ball Tips, Mailslot, Kickplates and Door Closers
- Multi-point Lock System

DEADBOLT PREP

- 2-1/8" Facebore located 5-1/2" on center above Lockset. Lockguard Security Plate included with deadbolt prep

STORM DOOR ADAPTER

- (for Sidelight Units) - Primed, Clear Pine and Clad Plus II

SINGLE DOOR UNIT

How-to-Order

Specify the following when ordering:

1. Door Design, number and size
2. Swing
 - Left or Right Hand
 - Inswing or Outswing
3. Wall Thickness **and** Jamb Type
 - 4-9/16" FJ Primed (Std.)
4. Aluminum Sill
 - Standard
5. Type of Casing
 - Primed Brickmould (Standard)
 - Flat Casing
 - Entrance Trim
6. Hardware Options

DOUBLE DOOR UNIT


How-to-Order

Specify the following when ordering:

1. Door Design, number and size
2. Swing
 - Left or Right Hand
 - Inswing or Outswing
3. Wall Thickness **and** Jamb Type
 - 4-9/16" FJ Primed (Std.)
4. Aluminum Sill
 - Standard
5. Type of Casing
 - Primed Brickmould (Standard)
 - Flat Casing
 - Entrance Trim
6. Hardware Options – Specify for one or both doors


HANDING - SINGLE DOOR

When the door opens toward you and the knob is on the left hand side, it is a LEFT HAND DOOR. When the knob is on the right, it is a RIGHT HAND DOOR.



HANDING - DOUBLE DOOR

When the door opens toward you and the knob is on the left hand side, it is a LEFT HAND DOOR. When the knob is on the right, it is a RIGHT HAND DOOR.



FITTING AND HANGING

1. When hanging the door, allow adequate clearance for swelling of door or frame in damp weather. Allow approximately 3/16" clearance from swelling when the door is installed in fully dry conditions. Jambs must be plumb.
2. Do not cut doors down in height by more than 2" (1-1/2" maximum from bottom or 1" on doors with UltraBlock® technology, 1/2" maximum from top). Care should be taken in cutting doors down in width to avoid exposing engineered components. Use a sharp fine-tooth saw for trimming ends of doors.
3. Caution must be used to avoid impairing the strength of the door when fitting for locks. Allow at least 1" of wood back of mortise.
4. Use three hinges on doors up to 7' in height and four hinges on doors over 7'. Hinges must be set in a straight line to prevent distortion.
5. Jambs and stops must be set square and plumb.
6. For best performance and to meet the standard Simpson warranty, any exterior door should be installed under an overhang or with sufficient protection. Adequate overhang depends on typical weather conditions of the area where the door is installed, but at the minimum means an overhang projecting a distance from the structure equal to one half the distance between the bottom of the door and the bottom of the overhang (see figure 1).
7. If an adequate overhang is not feasible, Simpson offers a selection of products warranted for this application, including a five-year limited warranty on doors featuring WaterBarrier® technology and a ten-year limited warranty on Nantucket® Collection doors.
8. Do not use dark colored stains or paints.
9. Immediately after cutting and fitting (before hanging), seal all cut surfaces and ends of door with an effective quality sealer. See exterior and interior finishing recommendation for complete instructions.
10. Prior to exterior exposure, doors must be finished with complete finish system.
11. To minimize heat loss and save energy, use weather stripping.




Figure 1

INSWING DOOR SYSTEM - STANDARD ALUMINUM SILL

- Oak & Mahogany Sill: ADD 1/2" to Height of all dimensions
- Public Access Aluminum Sill: Deduct 1" from Height of all dimensions

SIZE	ROUGH OPENING	UNIT DIMENSION NO CASING	UNIT DIMENSION W/ BRICKMOULD	UNIT DIMENSION W/ 1-9/16" x 3-1/2" FLAT CASING
2'-6" x 6'-8"	32-1/2" x 82-1/2"	31-3/8" x 81-3/4"	34" x 83"	37" x 83-1/2"
2'-8" x 6'-8"	34-1/2" x 82-1/2"	33-3/8" x 81-3/4"	36" x 83"	39" x 83-1/2"
3'-0" x 6'-8"	38-1/2" x 82-1/2"	37-3/8" x 81-3/4"	40" x 83"	43" x 83-1/2"
5'-0" x 6'-8"	63" x 82-1/2"	61-3/8" x 81-3/4"	64-1/2" x 83"	67-1/2" x 83-1/2"
5'-4" x 6'-8"	67" x 82-1/2"	65-3/8" x 81-3/4"	68-1/2" x 83"	71-1/2" x 83-1/2"
6'-0" x 6'-8"	75" x 82-1/2"	73-3/8" x 81-3/4"	76-1/2" x 83"	79-1/2" x 83-1/2"

For 8'-0" Height Units – add 16" to all height dimensions shown.

OUTSWING DOOR SYSTEM - STANDARD ALUMINUM SILL OR PUBLIC ACCESS SILL

- Oak & Mahogany Sill: ADD 3/4" to Height of all dimensions
- Public Access Aluminum Sill: Use Table AS IS

SIZE	ROUGH OPENING	UNIT DIMENSION NO CASING	UNIT DIMENSION W/ BRICKMOULD	UNIT DIMENSION W/ 1 1/16" x 3-1/2" FLAT CASING
2'-6" x 6'-8"	32-1/2" x 82-1/2"	31-3/8" x 81-3/8"	34-1/2" x 83-3/8"	37-1/2" x 83-3/8"
2'-8" x 6'-8"	34-1/2" x 82-1/2"	33-3/8" x 81-3/8"	36-1/2" x 83-3/8"	39-1/2" x 83-3/8"
3'-0" x 6'-8"	38-1/2" x 82-1/2"	37-3/8" x 81-3/8"	40-1/2" x 83-3/8"	43-1/2" x 83-3/8"
5'-0" x 6'-8"	63" x 82-1/2"	61-3/8" x 81-3/8"	65" x 83-3/8"	68" x 83-3/8"
5'-4" x 6'-8"	67" x 82-1/2"	65-3/8" x 81-3/8"	69" x 83-3/8"	72" x 83-3/8"
6'-0" x 6'-8"	75" x 82-1/2"	73-3/8" x 81-3/8"	77" x 83-3/8"	80" x 83-3/8"

For 8'-0" Height Units – add 16" to all height dimensions shown.

DOOR & SIDELIGHT UNIT _ INSWING DOOR SYSTEM - STANDARD ALUMINUM SILL MULL POST OR JAMB TO JAMB - SAME WIDTH DIMENSIONS

- Oak & Mahogany Sill: ADD 1/2" to Height of all dimensions
- Public Access Aluminum Sill: Deduct 1" from Height of all dimensions

SIZE	ROUGH OPENING	UNIT DIMENSION NO CASING	UNIT DIMENSION W/ BRICKMOULD	UNIT DIMENSION W/ 1 1/16" x 3-1/2" FLAT CASING
3'-0" x 6'-8" w/ (1) 10" Sdlt	50" x 82-1/2"	48-3/8" x 81-3/8"	51-1/2" x 83"	54-1/2" x 83-1/2"
3'-0" x 6'-8" w/ (1) 12" Sdlt	52" x 82-1/2"	50-3/8" x 81-3/8"	53-1/2" x 83"	56-1/2" x 83-1/2"
3'-0" x 6'-8" w/ (1) 14" Sdlt	54" x 82-1/2"	52-3/8" x 81-3/8"	55-1/2" x 83"	58-1/2" x 83-1/2"
3'-0" x 6'-8" w/ (2) 10" Sdlts	61-1/2" x 82-1/2"	60-3/8" x 81-3/8"	63-1/2" x 83"	66-1/2" x 83-1/2"
3'-0" x 6'-8" w/ (2) 12" Sdlts	65-1/2" x 82-1/2"	64-3/8" x 81-3/8"	67" x 83"	70" x 83-1/2"
3'-0" x 6'-8" w/ (2) 14" Sdlts	69-1/2" x 82-1/2"	68-3/8" x 81-3/8"	71" x 83"	74" x 83-1/2"

For Transom Unit Height add the Transom frame height to the appropriate dimension to obtain new height.

WARRANTIES

When you engineer doors designed to last generations, you can feel confident in assuring their durability. That's why Simpson doors are backed by some of the strongest warranties in the business. Enjoy peace-of-mind from our industry-leading warranties that are strong, secure and long-lasting ... like our doors.

SIMPSON® LIMITED WARRANTY

Simpson Door Company ("Simpson") warrants that each panel door bearing the Simpson brand and identification mark complies with Industry Standard NWWDA I.S.6. and all revisions in effect as of the date of manufacture, and Simpson further warrants, except as stated below, that each such door, at the time of the shipment from Simpson, is of good material and workmanship and free from defects that would render such door unserviceable or unfit for the ordinary, recommended use. The Simpson limited warranty applies to new doors other than those sold "as is". Warranty periods for specific doors and door components, and exclusions, follow:

ONE YEAR EXTERIOR DOOR AND FIRE DOOR WARRANTY

For doors used in an exterior application, other than as specified herein, and for fire-rated interior doors, this warranty shall survive for one year after the date of shipment from Simpson. This warranty applies to doors properly sealed, finished and, in the case of exterior applications, hung in a location protected from exposure to direct sun or rain under normal conditions. See specific Fitting and Hanging instructions.

TEN YEAR INTERIOR DOOR WARRANTY

For doors used in an interior application (defined as being exposed to controlled interior climactic conditions on both sides of the door), this warranty shall survive for ten years after the date of shipment from Simpson. This warranty applies to doors properly sealed, finished and hung. See specific Fitting and Hanging instructions. The ten year warranty on interior doors does not apply to fire-rated interior doors, doors with resin panels, or doors used in commercial, hospitality or multi-family applications, in which case, the one year warranty will apply. The ten year warranty applies only to the original end-user and is not transferable.

TEN YEAR NANTUCKET® COLLECTION LIMITED WARRANTY

For Nantucket Collection doors—defined as using Nantucket construction methods—in Sapele Mahogany, Douglas Fir or Nootka Cypress wood species, this warranty shall survive for ten years after the date of shipment from Simpson. This warranty applies to doors properly sealed and finished per Simpson's Care and Finishing instructions. The ten year warranty on Nantucket Collection doors does not apply to doors used in commercial, hospitality or multi-family applications. Further, face-checking is considered a natural characteristic and shall not be considered a defect. The ten year warranty applies only to the original end-user and is not transferable.

FIVE YEAR PERFORMANCE SERIES® WITH WATERBARRIER® TECHNOLOGY DOOR LIMITED WARRANTY

For all doors that include WaterBarrier technology over the exterior surface of the door, this warranty shall survive for five years after the date of shipment from Simpson. This warranty applies to doors properly sealed and finished per Simpson's Care and Finishing instructions. The five year warranty on doors with WaterBarrier technology does not apply to doors used in commercial, hospitality or multi-family applications. The five year warranty applies only to the original end-user and is not transferable.

FIVE YEAR PERFORMANCE SERIES® WITH ULTRABLOCK® TECHNOLOGY DOOR LIMITED WARRANTY

For all doors that include UltraBlock technology in the bottom of the door stiles, this warranty shall survive for five years after the date of shipment from Simpson. This warranty applies to the stiles and bottom rails of doors properly sealed, finished and, in the case of exterior applications, hung in a location protected from exposure to direct sun or rain under normal conditions. See specific Fitting and Hanging instructions. Other door components are subject to Simpson's one year limited warranty.

FIVE YEAR LIMITED INSULATED GLASS WARRANTY

Simpson Door Company warrants that standard clear insulated glass units will not, for a period of five (5) years after the date of shipment from Simpson, develop material obstruction of vision between the interior glass surfaces caused by failure of the hermetic seal. This warranty shall not apply to units with broken glass, glass units installed by others, or units that have retrofit films applied.

Simpson's liability under this warranty shall be limited to shipping a replacement glass unit.

LIMITED LIFETIME INNERBOND® WARRANTY

Simpson further provides a limited lifetime warranty on Innerbond panels against splitting through the entire panel due to rain, sun, weather, and other such factors exclusive of major calamity.

In the event an Innerbond panel splits through, Simpson will ship a replacement door. If Simpson has discontinued manufacturing the door type/style with the Innerbond panel warranty claim, Simpson will issue a replacement door equal to or less than the original price of the original door purchase.

For more information on these warranties, please visit: simpsondoor.com/warranties

SIMPSON SPECIAL ORDER AND CONCEPT® CUSTOM DOORS

If you haven't found what you are looking for in this brochure, let your BROSCO representative help you create a one-of-a-kind door to fit your needs. From species selection to design, BROSCO and Simpson can guide you through the process of creating a custom door. And you will receive the same great service and attention to detail you'd expect from both.



BROSCO.COM



#BuiltByBROSCO

Simpson[®]
Door Company

SIMPSONDOOR.COM