



LAYERS OF PROTECTION: ZIP SYSTEM™ ROOF ASSEMBLY LEAK-FREE GUARANTEE*

When you register and combine revolutionary ZIP System® sheathing, tape and peel and stick underlayment, you can receive multiple layers of protection against damaging water leaks that can occur from ice or wind-driven rain. Register your eligible project at: LeakFreeGuarantee.com/Register

Roof assemblies built with ZIP System® sheathing and tape or ZIP System™ peel and stick underlayment may be eligible for designation as a FORTIFIED Roof™ sealed roof deck. FORTIFIED™ is a voluntary set of above-code design, building and retrofitting standards developed by the Insurance Institute for Business & Home Safety to strengthen homes against severe weather. A FORTIFIED Roof™ designation requires a successful evaluation and compliance with all IBHS program requirements. IBHS is not responsible or liable for the performance of ZIP System™ products. [Learn more at Fortifiedhome.org/roof](http://Fortifiedhome.org/roof).



LEAK-FREE GUARANTEE*
WHEN USED WITH
ZIP SYSTEM® SHEATHING AND TAPE



**SEALS AROUND
NAILS**




SLIP-RESISTANT



**AVAILABLE IN
STANDARD AND HIGH
TEMP FORMULATIONS**

*Registration Required. Leak-Free Guarantee applies only when using a ZIP System Roof Assembly. See LeakFreeGuarantee.com for details and the definition of a ZIP System Roof Assembly.

- Use to meet code requirements for ice barrier or as a roofing underlayment in accordance with ESR-4904
- High-performance self-adhered rubberized asphalt product that seals around nails
- Embedded pull cord splits liner on demand
- Use to protect areas at risk of leaks or water damage due to ice dams or wind-driven rain, such as at eaves and valleys, or in entire roof applications
- Tested in accordance with ASTM D 1970
- Slip-resistant surface for ease of application
- Waterproofing roof underlayment



LEAK-FREE GUARANTEE*
WHEN USED WITH ZIP SYSTEM® SHEATHING AND TAPE

*Registration Required. Leak-Free Guarantee applies only when using a ZIP System Roof Assembly. See LeakFreeGuarantee.com for details and the definition of a ZIP System Roof Assembly.

ZIP SYSTEM™ PEEL AND STICK UNDERLAYMENT

TYPE	TOTAL COVERAGE	WIDTH	ADHESIVE TECHNOLOGY	CODE EVALUATION REPORT	SERVICE TEMPERATURE APPLICATION	EXPOSURE	SHELF LIFE	PERMEANCE
Standard	200 ft ²	36" x 66'	Rubberized Asphalt	ESR-4904	180° F	90 days	12 mo.	ASTM E96 ≤ 0.05 perms
High Temperature					240° F	120 days		